

FORD (EU) TRANSIT V363 TRANSIT 2.2 TDCI (125) RWD (2014-2018)



MOTOR CYR5

Kapacitet: 10,5 liter (Førstegangsupfyldning), Kapacitet: 10,1 liter (Servicepåfyldning)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Duranza LSP 5W-30

Kontroller alle 25000 km/ 12 måneder, skift alle 50000 km/ 24 måneder

DIFFERENTIALE BAG

Kapacitet: 2,85 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

SP Gear 1071

Kontroller alle 25000 km/ 12 måneder, skift alle 50000 km/ 24 måneder

GEAR MANUEL MT82 6/1

Kapacitet: 2,3 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

SP Gear 1081

Kontroller alle 50000 km/ 24 måneder

HYDRAULISK BREMSE- & KOBLINGSSYSTEM

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

Kontroller alle 25000 km/ 12 måneder, skift alle 24 måneder

SERVOSTYRING

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

SP Matic 4036

PRODUKTANBEFALING 2

SP Matic 2032

Kontroller alle 50000 km/ 24 måneder

FORD (EU) TRANSIT V363 TRANSIT 2.2 TDCI (125) RWD (2014-2018)



KØLESYSTEM

Kapacitet: 10-13 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

PRODUKTANBEFALING 3

Coolant -38 Organic NF

Kontroller alle 50000 km/ 24 måneder, skift alle 120 måneder

AIRCONDITIONSYSTEM BUS

Kapacitet: 725-755 gram, Kapacitet: 1035-1065 gram (med hjælpeklimakontrol)

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

KLIMAANLÆGSKOMPRESSOR BUS

Kapacitet: 160-245 cm³

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

KLIMAANLÆGSKOMPRESSOR VAREVOGN

Kapacitet: 160-245 cm³

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

KLIMAANLÆGSSYSTEM

Kapacitet: 725-765 gram, Kapacitet: 1135-1165 gram (med 2-zoners airconditionssystem)

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.