

FORD (USA) F-150, 12TH GEN. F-150 3.7 V6 TI-VCT (2010-2011)



MOTOR Duratec 37
Kapacitet: 5,7 liter

ANVEND

Krævende

KLIMA

Moderat

PRODUKTANBEFALING 1

Duranza ECO 5W-20

Kontroller alle 1 måneder, skift alle 5000 mil/ 6 måneder

ANVEND

Fleksibel (max)

KLIMA

Moderat

PRODUKTANBEFALING 1

Duranza ECO 5W-20

Kontroller alle 1 måneder, skift alle 10000 mil/ 12 måneder

DIFFERENTIALE BAG

Kapacitet: 2,6 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube Racing 75W-140

Skift alle 150000 mil

GEAR AUTOMATISK 6R80 6/1

Kapacitet: 11,7 liter (Tør efterfyld)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Matic 4036

PRODUKTANBEFALING 2

SP Matic 2032

Skift alle 150000 mil

SELVSPÆRRENDE DIFFERENTIALE BAG

Kapacitet: 2,6 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube Racing 75W-140

Skift alle 150000 mil

FORD (USA) F-150, 12TH GEN. F-150 3.7 V6 TI-VCT (2010-2011)



HYDRAULISK BREMSESYSTEM

Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid DOT 3

KØLESYSTEM

Kapacitet: 15,1 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

PRODUKTANBEFALING 3

Coolant -38 Organic NF

Kontroller alle 6 måneder, skift alle 50000 mil/ 36 måneder

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

PRODUKTANBEFALING 3

Coolant -38 Organic NF

Kontroller alle 6 måneder, skift alle 100000 mil/ 72 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.