

FORD (USA) F-450 (SUPER DUTY) F-450 5.4 V8 SUPER DUTY (2008-2010)



MOTOR Triton
Kapacitet: 6,6 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Duranza ECO 5W-20

Kontroller alle 1 måneder, skift alle 7500 mil/ 6 måneder

ANVEND	KLIMA
Krævende	Moderat

PRODUKTANBEFALING 1

Duranza ECO 5W-20

Kontroller alle 1 måneder, skift alle 5000 mil/ 6 måneder/ 200 timer

DIFFERENTIALE BAG Dana S110/S130
Kapacitet: 6,6 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Gearlube Racing 75W-140

Skift alle 105000 mil

ANVEND	KLIMA
Krævende	Moderat

PRODUKTANBEFALING 1

Gearlube Racing 75W-140

Skift alle 50000 mil

GEAR AUTOMATISK TorqShift 5R110 5/1
Kapacitet: 16,6 liter (Tør efterfyld)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

SP Matic 4036

PRODUKTANBEFALING 2

SP Matic 2032

Kontroller alle 15000 mil, skift alle 60000 mil

ANVEND	KLIMA
Krævende	Moderat

PRODUKTANBEFALING 1

SP Matic 4036

PRODUKTANBEFALING 2

SP Matic 2032

Skift alle 30000 mil

FORD (USA) F-450 (SUPER DUTY) F-450 5.4 V8 SUPER DUTY (2008-2010)



GEAR MANUEL S6-650 6/1

Kapacitet: 5,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Matic 2032

Skift alle 105000 mil

ANVEND

Krævende

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Matic 2032

Skift alle 50000 mil

HYDRAULISK BREMSESYSTEM

Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid DOT 3

HYDRAULISK KOBLINGSSYSTEM

Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid DOT 3

SERVOSTYRING

Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Matic 2032

FORD (USA) F-450 (SUPER DUTY) F-450 5.4 V8 SUPER DUTY (2008-2010)



KØLESYSTEM

Kapacitet: 25,3 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 12

PRODUKTANBEFALING 2

Coolant SP 11

Kontroller alle 6 måneder, skift alle 45000 mil/ 36 måneder

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 12

PRODUKTANBEFALING 2

Coolant SP 11

Kontroller alle 6 måneder, skift alle 105000 mil/ 72 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.