

HYUNDAI (EU) H 300 TQ (NL) H 300 2.4 MPI (2007-2009)



MOTOR

Kapacitet: 4,3 liter, Kapacitet: 4,4 liter (+ olieøkøler)

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Bi-Turbo 20W-50	Multifleet SHPD 20W-50	

Skift alle 15000 km/ 12 måneder

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Duranza ECO 5W-20	Duranza LSP 5W-30	Asyntho 5W-30

Skift alle 15000 km/ 12 måneder

ANVEND	KLIMA
Krævende	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Bi-Turbo 20W-50	Multifleet SHPD 20W-50	

Skift alle 7500 km/ 6 måneder

ANVEND	KLIMA
Krævende	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Duranza ECO 5W-20	Duranza LSP 5W-30	Asyntho 5W-30

Skift alle 7500 km/ 6 måneder

DIFFERENTIALE BAG

Kapacitet: 1,8-2,4 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-4 80W-90	Unigear HS GL-3/GL-5 80W-90	

Kontroller alle 24 måneder/ 30000 km

ANVEND	KLIMA
Krævende	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-4 80W-90	Unigear HS GL-3/GL-5 80W-90	

Kontroller alle 30000 km/ 24 måneder, skift alle 90000 km

HYUNDAI (EU) H 300 TQ (NL) H 300 2.4 MPI (2007-2009)



GEAR AUTOMATISK 4/1

Kapacitet: 8 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Matic 4026	ATF Dexron II-D	

Kontroller alle 15000 km/ 12 måneder, skift alle 90000 km/ 72 måneder

ANVEND		KLIMA
Krævende		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Matic 4026	ATF Dexron II-D	

Kontroller alle 15000 km/ 12 måneder, skift alle 40000 km

GEAR MANUEL 5/1

Kapacitet: 1,95 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
SP Gear 5015	Syngear MT/LD 75W-80	Syngear 75W-90

Kontroller alle 15000 km/ 12 måneder

ANVEND		KLIMA
Krævende		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
SP Gear 5015	Syngear MT/LD 75W-80	Syngear 75W-90

Kontroller alle 15000 km/ 12 måneder, skift alle 100000 km

HYDRAULISK BREMSE- & KOBLINGSSYSTEM

Kapacitet: 0,7-0,8 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3

Kontroller alle 15000 km/ 12 måneder

HYUNDAI (EU) H 300 TQ (NL) H 300 2.4 MPI (2007-2009)



SERVOSTYRING

Kapacitet: 0,9-1 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

ATF Dexron II-D

Kontroller alle 15000 km/ 12 måneder

KØLESYSTEM

Kapacitet: 7,1-10,2 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

Skift alle 40000 km/ 24 måneder

ANVEND

Første skift kun

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

Skift alle 100000 km/ 60 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.