

HYUNDAI (EU) HD65/72 HD65 D4DC EURO 1 (2004-2010)



MOTOR Hyundai D4DC
Kapacitet: 9,3 liter, Filterkapacitet: 0,3 liter

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1		
Multifleet SCD 30		

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Asyntho 5W-30	Bi-Turbo 15W-40	Synfleet SHPD 10W-40

ANVEND	KLIMA
Normal	Koldt

PRODUKTANBEFALING 1		
Armado Synth 5W-30		

DIFFERENTIALE BAG
Kapacitet: 4,5 liter

ANVEND	KLIMA
Normal	Tropisk

PRODUKTANBEFALING 1		
Gearlube GL-5 85W-140		

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

GEAR MANUEL M035S5 5/1
Kapacitet: 3,2 liter, Kapacitet: 3,7 liter (+ kraftudtag)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
SP Gear 5015	Gearlube GL-4 80W	Gearlube GL-4 80W-90

HYUNDAI (EU) HD65/72 HD65 D4DC EURO 1 (2004-2010)



GEAR MANUEL M2S5 5/1 Kapacitet: 4 liter, Kapacitet: 4,5 liter (+ kraftudtag)		
ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
SP Gear 5015	Gearlube GL-4 80W	Gearlube GL-4 80W-90

GEAR MANUEL M3S5 5/1 Kapacitet: 3,4 liter, Kapacitet: 3,9 liter (+ kraftudtag)		
ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
SP Gear 5015	Gearlube GL-4 80W	Gearlube GL-4 80W-90

HYDRAULISK BREMSE- & KOBLINGSSYSTEM Kapacitet: 0,3 liter		
ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Drauliquid-S DOT 4		

SERVOSTYRING Kapacitet: 1,2 liter		
ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
ATF Dexron II-D		

SMØREPUNKTER/NIPLER HJULLEJER FOR		
ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2	

HYUNDAI (EU) HD65/72 HD65 D4DC EURO 1 (2004-2010)



KØLESYSTEM

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26

STYREHUS

Kapacitet: 0,9 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

ATF Dexron II-D

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.