

HYUNDAI (EU) TUCSON JM TUCSON 2.0 CRDI 16V (2004-2009)



MOTOR D4EA

Kapacitet: 5,9 liter, Filterkapacitet: 0,5 liter

ANVEND

Normal

KLIMA

Middelhavsgtigt

PRODUKTANBEFALING 1

Multifleet SCD 30

Skift alle 15000 km/ 12 måneder

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Asyntho 5W-30

PRODUKTANBEFALING 2

Bi-Turbo 15W-40

PRODUKTANBEFALING 3

Synfleet SHPD 10W-40

Skift alle 15000 km/ 12 måneder

ANVEND

Normal

KLIMA

Koldt

PRODUKTANBEFALING 1

Armado Synth 5W-30

Skift alle 15000 km/ 12 måneder

DIFFERENTIALE BAG 4x4

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Kontroller alle 15000 km/ 12 måneder

REDUKTIONSGEARKASSE

Kapacitet: 0,8 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Kontroller alle 40000 km, skift alle 100000 km

HYUNDAI (EU) TUCSON JM TUCSON 2.0 CRDI 16V (2004-2009)



TRANSAKSEL AUTOMATISK F4A42-1/2 4/1

Kapacitet: 7,8 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
SP Matic 4026		

Kontroller alle 30000 km/ 24 måneder, skift alle 90000 km/ 72 måneder

TRANSAKSEL MANUEL M5GF1 5/1

Kapacitet: 2,15 liter

ANVEND	KLIMA
->2005	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
SP Gear 1011	Syngear TDL 75W-90	Syngear 75W-90

Kontroller alle 15000 km/ 12 måneder

ANVEND	KLIMA
2005->	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
SP Gear 5015	Syngear MT/LD 75W-80	Syngear 75W-90

Kontroller alle 15000 km/ 12 måneder

TRANSAKSEL MANUEL M6GF2 6/1

Kapacitet: 1,9 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
SP Gear 5015	Syngear MT/LD 75W-80	Syngear 75W-90

Kontroller alle 20000 km/ 12 måneder

ANVEND	KLIMA
Krævende	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
SP Gear 5015	Syngear MT/LD 75W-80	Syngear 75W-90

Skift alle 100000 km

HYUNDAI (EU) TUCSON JM TUCSON 2.0

CRDI 16V (2004-2009)



HYDRAULISK BREMSE- & KOBLINGSSYSTEM

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4

PRODUKTANBEFALING 3

Drauliquid DOT 3

Kontroller alle 15000 km/ 12 måneder

SERVOSTYRING

Kapacitet: 0,9 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

ATF Dexron II-D

KØLESYSTEM

Kapacitet: 7,9 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26

Kontroller alle 15000 km/ 12 måneder, skift alle 30000 km/ 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.