



MOTOR F1AE3481B

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Presteza MSP 5W-30	Avanza MSP+ 5W-30	Avanza RPC 5W-30

Skift alle 40000 km/ 24 måneder/ 800 timer

ANVEND	KLIMA
Krævende	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Presteza MSP 5W-30	Avanza MSP+ 5W-30	Avanza RPC 5W-30

Skift alle 20000 km/ 12 måneder

ANVEND	KLIMA
Svovlniveau i brændstof > 0,5 %	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Presteza MSP 5W-30	Avanza MSP+ 5W-30	Avanza RPC 5W-30

Skift alle 20000 km

DIFFERENTIALE BAG

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Skift alle 80000 km/ 24 måneder

ANVEND	KLIMA
Normal	Arktisk

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Skift alle 80000 km/ 24 måneder

GEAR AUTOMATISK ZF 6AS-400 6/1

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Syngear MT/LD 75W-80		

Skift alle 120000 km/ 2400 timer/ 36 måneder



GEAR MANUEL 2830.5 5/1

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Gear 5015	Syngear MT/LD 75W-80	

Skift alle 120000 km/ 2400 timer/ 36 måneder

GEAR MANUEL FPT 2835.6 6/1

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Gear 5015	Syngear MT/LD 75W-80	

Skift alle 120000 km/ 2400 timer/ 36 måneder

HYDRAULISK BREMSESYSTEM

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Kontroller alle 40000 km/ 800 timer, skift alle 24 måneder

SERVOSTYRING

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
ATF Dexron II-D		

SMØREPUNKTER/NIPLER HJULLEJER

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Labora Grease	Multi Purpose Grease 3	

**KØLESYSTEM BLÅ VÆSKE**

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 11*Kontroller alle 12 måneder, skift alle 36 måneder***KØLESYSTEM GUL VÆSKE**

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

PRODUKTANBEFALING 3

Coolant -38 Organic NF*Kontroller alle 12 måneder, skift alle 36 måneder*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.