

IVECO DAILY 30 DAILY 30 S 13 (2014-2016)**ENGINE F1AFL411B**

Capacity: 4,3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Duranza MSP 0W-30	Presteza MSP 0W-30	Avanza MSP 0W-30

Change every 40000 km/ 24 months/ 800 hours

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Duranza MSP 0W-30	Presteza MSP 0W-30	Avanza MSP 0W-30

Change every 20000 km/ 12 months

USE		CLIMATE
Fuel sulfur level >0,5%		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Duranza MSP 0W-30	Presteza MSP 0W-30	Avanza MSP 0W-30

*Change every 20000 km/ 12 months***DIFFERENTIAL REAR NDA R.S.**

Capacity: 1,35 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Change every 80000 km/ 24 months/ 1600 hours

USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

*Change every 80000 km/ 24 months/ 1600 hours***TRANSMISSION AUTOMATED ZF 6AS-400A OD 6/1**

Capacity: 2,2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	Syngear MT/LD 75W-80	

Change every 120000 km/ 2400 hours/ 36 months

IVECO DAILY 30 DAILY 30 S 13 (2014-2016)**TRANSMISSION MANUAL** FPT 2835.6 DOD 6/1

Capacity: 2,2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	Syngear MT/LD 75W-80	

*Change every 120000 km/ 2400 hours/ 36 months***HYDRAULIC BRAKE SYSTEM**

Capacity: 1,11 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

*Check every 40000 km/ 12 months/ 800 hours, change every 24 months***POWER STEERING**

Capacity: 1,3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		

GREASE POINTS/NIPPLES WHEEL BEARINGS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Labora Grease	Multi Purpose Grease 3	

COOLING SYSTEM

Capacity: 16 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Check every 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.