

## IVECO DAILY 35 DAILY 35 C 10 P (2006-2009)

**MOTOR F1AE0481A-HPI**

Kapacitet: 5,7 liter, Filterkapacitet: 1,4 liter (+ varmeveksler)

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1      | PRODUKTANBEFALING 2  |
|--------------------------|----------------------|
| <b>Duranza LSP 5W-30</b> | <b>Asyntho 5W-30</b> |

Skift alle 40000 km/ 800 timer/ 12 måneder

| ANVEND                  | KLIMA   |
|-------------------------|---------|
| Alternativ (acceptabel) | Moderat |

| PRODUKTANBEFALING 1           | PRODUKTANBEFALING 2           |
|-------------------------------|-------------------------------|
| <b>Dieselfleet CD+ 15W-40</b> | <b>Multifleet SHPD 15W-40</b> |

Skift alle 40000 km/ 800 timer/ 12 måneder

**DIFFERENTIALE BAG NDA R.G.**

Kapacitet: 1,9 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1          | PRODUKTANBEFALING 2                 |
|------------------------------|-------------------------------------|
| <b>Gearlube GL-5 85W-140</b> | <b>Unigear LS GL-3/GL-5 85W-140</b> |

Kontroller alle 40000 km/ 12 måneder/ 800 timer, skift alle 80000 km/ 24 måneder/ 1600 timer

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Arktisk |

| PRODUKTANBEFALING 1         | PRODUKTANBEFALING 2                |
|-----------------------------|------------------------------------|
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |

Kontroller alle 40000 km/ 12 måneder/ 800 timer, skift alle 80000 km/ 24 måneder/ 1600 timer

**GEAR MANUEL ZF 5S-300 5/1**

Kapacitet: 2 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1 | PRODUKTANBEFALING 2         |
|---------------------|-----------------------------|
| <b>SP Gear 5015</b> | <b>Syngear MT/LD 75W-80</b> |

Kontroller alle 40000 km/ 12 måneder/ 800 timer, skift alle 120000 km/ 36 måneder/ 2400 timer

**HYDRAULISK BREMSESYSTEM**

Kapacitet: 1,11 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Drauliquid-LV Super DOT 4**

PRODUKTANBEFALING 2

**Drauliquid-S DOT 4***Kontroller alle 40000 km/ 12 måneder/ 800 timer, skift alle 24 måneder***HYDRAULISK KOBLINGSSYSTEM**

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Drauliquid-LV Super DOT 4**

PRODUKTANBEFALING 2

**Drauliquid-S DOT 4***Kontroller alle 40000 km/ 12 måneder/ 800 timer, skift alle 24 måneder***SERVOSTYRING**

Kapacitet: 1,4 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**ATF Dexron II-D***Kontroller alle 40000 km/ 12 måneder/ 800 timer***KØLESYSTEM**

Kapacitet: 9 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Coolant -38 Organic NF**

PRODUKTANBEFALING 2

**Coolant -26***Kontroller alle 12 måneder, skift alle 36 måneder*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.