

**MOTOR F1AE0481B-HPI**

Kapacitet: 5,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Armado Synth 5W-30

PRODUKTANBEFALING 2

Dieselfleet CD+ 15W-40

PRODUKTANBEFALING 3

Multifleet SHPD 15W-40*Skift alle 40000 km/ 800 timer/ 12 måneder***DIFFERENTIALE BAG 4517**

Kapacitet: 1,85 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 85W-140

PRODUKTANBEFALING 2

Unigear LS GL-3/GL-5 85W-140*Skift alle 120000 km/ 2400 timer/ 36 måneder*

ANVEND

Normal

KLIMA

Arktisk

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90*Skift alle 120000 km/ 2400 timer/ 36 måneder***GEAR MANUEL ZF 5S-200 5/1**

Kapacitet: 2 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 5015

PRODUKTANBEFALING 2

Syngear MT/LD 75W-80*Skift alle 120000 km/ 2400 timer/ 36 måneder***HYDRAULISK BREMSESYSTEM**

Kapacitet: 1,1 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4*Kontroller alle 40000 km/ 12 måneder/ 800 timer, skift alle 24 måneder*

**SERVOSTYRING ZF 8090**

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

ATF Dexron II-D*Kontroller alle 40000 km/ 12 måneder/ 800 timer***SMØREPUNKTER/NIPLER ANDRE**

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2**SMØREPUNKTER/NIPLER HJULLEJER**

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Multi Purpose Grease 3**KØLESYSTEM**

Kapacitet: 9 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26*Kontroller alle 12 måneder, skift alle 36 måneder*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.