



MOTOR 8140.43S
Kapacitet: 6,3 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Bi-Turbo 15W-40

PRODUKTANBEFALING 2

Armado Synth 5W-30

PRODUKTANBEFALING 3

Dieselfleet CD+ 15W-40

Skift alle 30000 km/ 600 timer/ 12 måneder

DIFFERENTIALE BAG 4517
Kapacitet: 1,85 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 85W-140

PRODUKTANBEFALING 2

Unigear LS GL-3/GL-5 85W-140

Skift alle 120000 km/ 2400 timer/ 36 måneder

ANVEND
Normal

KLIMA
Arktisk

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Skift alle 120000 km/ 2400 timer/ 36 måneder

GEAR MANUEL ZF 6S-300 6/1
Kapacitet: 2,7 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

SP Gear 5015

PRODUKTANBEFALING 2

Syngear MT/LD 75W-80

Skift alle 120000 km/ 2400 timer/ 36 måneder

HYDRAULISK BREMSESYSTEM
Kapacitet: 1,1 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4

Kontroller alle 30000 km/ 12 måneder/ 600 timer, skift alle 24 måneder

**SERVOSTYRING ZF 8090**
 ANVEND
Normal

 KLIMA
Moderat

PRODUKTANBEFALING 1

ATF Dexron II-D
Kontroller alle 30000 km/ 12 måneder/ 600 timer
SMØREPUNKTER/NIPLER ANDRE
 ANVEND
Normal

 KLIMA
Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2**SMØREPUNKTER/NIPLER HJULLEJER**
 ANVEND
Normal

 KLIMA
Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Multi Purpose Grease 3**KØLESYSTEM**

Kapacitet: 9 liter

 ANVEND
Normal

 KLIMA
Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26
Kontroller alle 12 måneder, skift alle 36 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.