

IVECO DAILY 40 DAILY 40 C 10 P (2009-2011)



MOTOR F1AE0481A-HPI

Kapacitet: 5,7 liter, Filterkapacitet: 1,4 liter (+ varmeveksler)

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Presteza MSP 5W-30	Avanza MSP+ 5W-30	Avanza RPC 5W-30

Skift alle 40000 km/ 800 timer/ 12 måneder

DIFFERENTIALE BAG (4x2) 450511

Kapacitet: 1,9 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Kontroller alle 40000 km/ 12 måneder/ 800 timer, skift alle 80000 km/ 24 måneder/ 1600 timer

ANVEND		KLIMA
Normal		Arktisk
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Kontroller alle 40000 km/ 12 måneder/ 800 timer, skift alle 80000 km/ 24 måneder/ 1600 timer

GEAR MANUEL ZF 5S-300 5/1

Kapacitet: 2 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Gear 5015	Syngear MT/LD 75W-80	

Kontroller alle 40000 km/ 12 måneder/ 800 timer, skift alle 120000 km/ 36 måneder/ 2400 timer

HYDRAULISK BREMSESYSTEM

Kapacitet: 1,11 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Kontroller alle 40000 km/ 12 måneder/ 800 timer, skift alle 24 måneder

IVECO DAILY 40 DAILY 40 C 10 P (2009-2011)



SERVOSTYRING

Kapacitet: 1,4 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

ATF Dexron II-D

Kontroller alle 40000 km/ 12 måneder/ 800 timer

KØLESYSTEM

Kapacitet: 9 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26

Kontroller alle 12 måneder, skift alle 36 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.