IVECO DAILY 40 DAILY 40 C 15 P (2006-2009)



ENGINE F1C HPI Capacity: 7,6 liter, Filter capacity: 1 liter (+ heat exchanger)			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Duranza LSP 5W-30	Asyntho 5W-30		
Change every 40000 km/ 800 hours/ 12 m	nonths		
USE		CLIMATE	
Alternative (acceptable)		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40		

Change every 40000 km/800 hours/12 months

DIFFERENTIAL REAR (4x2) 450511 Capacity: 1,9 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Check every 40000 km/ 12 months/ 800 hours, change every 80000 km/ 24 months/ 1600 hours

TRANSMISSION MANUAL ZF 6S-400 OD 6/1 Capacity: 2,2 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Gear 5015	Syngear MT/LD 75W-80		
01 1 100001 110	/0001 / 00	4 /0.400 /	

Check every 40000 km/ 12 months/ 800 hours, change every 120000 km/ 36 months/ 2400 hours

HYDRAULIC BRAKE SYSTEM Capacity: 1,11 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	
Check every 40000 km/ 12 months/ 80	00 hours, change every 24 months	,

IVECO DAILY 40 DAILY 40 C 15 P (2006-2009)



POWER STEERING Capacity: 1,4 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		
Check every 40000 km/ 12 months/ 800	hours	

COOLING SYSTEM Capacity: 9 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Check every 12 months, change every 36 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.