

IVECO DAILY 60 DAILY 60 C 14 V EEV (2009-2011)



MOTOR F1C		
ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Presteza MSP 5W-30	Avanza MSP+ 5W-30	Avanza RPC 5W-30
Skift alle 40000 km/ 800 timer		

DIFFERENTIALE BAG		
ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	
Skift alle 80000 km/ 24 måneder/ 1600 timer		

ANVEND		KLIMA
Normal		Arktisk
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
Skift alle 80000 km/ 24 måneder/ 1600 timer		

GEAR AUTOMATISK ZF 6AS-400 6/1 Kapacitet: 2,2 liter		
ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Syngear MT/LD 75W-80		
Skift alle 120000 km/ 2400 timer		

GEAR MANUEL Iveco 2840.6 6/1		
ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Gear 5015	Syngear MT/LD 75W-80	
Skift alle 120000 km/ 2400 timer		

IVECO DAILY 60 DAILY 60 C 14 V EEV (2009-2011)



HYDRAULISK BREMSESYSTEM

Kapacitet: 1,1 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4

Kontroller alle 40000 km/ 800 timer, skift alle 24 måneder

HYDRAULISK KOBLINGSSYSTEM

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4

SERVOSTYRING

Kapacitet: 1,4 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

ATF Dexron II-D

Kontroller alle 40000 km/ 800 timer

KØLESYSTEM

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 11

Kontroller alle 12 måneder, skift alle 36 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.