

IVECO DAILY 65 DAILY 65 C 18 D (2006-2009)



MOTOR F1C HPT
Kapacitet: 7,6 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Duranza LSP 5W-30	Asyntho 5W-30	

Skift alle 40000 km/ 800 timer/ 12 måneder

DIFFERENTIALE BAG (4x2) 450517/2
Kapacitet: 3 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Kontroller alle 40000 km/ 12 måneder/ 800 timer, skift alle 80000 km/ 24 måneder/ 1600 timer

ANVEND	KLIMA
Normal	Arktisk

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Kontroller alle 40000 km/ 12 måneder/ 800 timer, skift alle 80000 km/ 24 måneder/ 1600 timer

GEAR MANUEL ZF 6S-400 OD 6/1
Kapacitet: 2,2 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Gear 5015	Syngear MT/LD 75W-80	

Kontroller alle 40000 km/ 12 måneder/ 800 timer, skift alle 120000 km/ 36 måneder/ 2400 timer

HYDRAULISK BREMSESYSTEM
Kapacitet: 1,1 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Skift alle 24 måneder

IVECO DAILY 65 DAILY 65 C 18 D (2006-2009)



SERVOSTYRING

Kapacitet: 1,4 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

ATF Dexron II-D

Kontroller alle 40000 km/ 12 måneder/ 800 timer

KØLESYSTEM

Kapacitet: 9 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26

Kontroller alle 12 måneder, skift alle 36 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.