

IVECO DAILY 65 DAILY 65 C 21 (2014-2016)



MOTOR F1CFL411

Kapacitet: 6,6 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Duranza MSP 0W-30

PRODUKTANBEFALING 2

Presteza MSP 0W-30

PRODUKTANBEFALING 3

Avanza MSP 0W-30

Skift alle 40000 km/ 24 måneder/ 800 timer

ANVEND

Krævende

KLIMA

Moderat

PRODUKTANBEFALING 1

Duranza MSP 0W-30

PRODUKTANBEFALING 2

Presteza MSP 0W-30

PRODUKTANBEFALING 3

Avanza MSP 0W-30

Skift alle 20000 km/ 400 timer/ 12 måneder

ANVEND

Svovlniveau i brændstof > 0,5 %

KLIMA

Moderat

PRODUKTANBEFALING 1

Duranza MSP 0W-30

PRODUKTANBEFALING 2

Presteza MSP 0W-30

PRODUKTANBEFALING 3

Avanza MSP 0W-30

Skift alle 20000 km/ 400 timer/ 12 måneder

DIFFERENTIALE BAG (4x2) 450517/2

Kapacitet: 3,1 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 85W-140

PRODUKTANBEFALING 2

Unigear LS GL-3/GL-5 85W-140

Skift alle 80000 km/ 24 måneder/ 1600 timer

ANVEND

Normal

KLIMA

Arktisk

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Skift alle 80000 km/ 24 måneder/ 1600 timer

GEAR AUTOMATISK ZF 8HP (HI-MATIC) 8/1

Kapacitet: 3,5-5 liter (Servicepåfyldning), Kapacitet: 9,5 liter (Tør efterfyld)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Matic 2034

Skift alle 200000 km/ 4000 timer



GEAR MANUEL FPT 2850.6 DOD 6/1
Kapacitet: 2 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Gear 5015	Syngear MT/LD 75W-80	

Skift alle 120000 km/ 2400 timer/ 36 måneder

HYDRAULISK BREMSESYSTEM
Kapacitet: 1,11 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Kontroller alle 40000 km/ 12 måneder/ 800 timer, skift alle 24 måneder

SERVOSTYRING
Kapacitet: 1,3 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
ATF Dexron II-D		

SMØREPUNKTER/NIPLER HJULLEJER

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Labora Grease	Multi Purpose Grease 3	

KØLESYSTEM
Kapacitet: 16 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Kontroller alle 12 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.