

## IVECO DAILY 72 DAILY 72 C 15 (2014-2016)



**ENGINE F1CFL411**  
Capacity: 6,6 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2  | PRODUCT RECOMMENDATION 3 |
|--------------------------|---------------------------|--------------------------|
| <b>Duranza MSP 0W-30</b> | <b>Presteza MSP 0W-30</b> | <b>Avanza MSP 0W-30</b>  |

Change every 40000 km/ 24 months/ 800 hours

| USE    | CLIMATE  |
|--------|----------|
| Severe | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2  | PRODUCT RECOMMENDATION 3 |
|--------------------------|---------------------------|--------------------------|
| <b>Duranza MSP 0W-30</b> | <b>Presteza MSP 0W-30</b> | <b>Avanza MSP 0W-30</b>  |

Change every 20000 km/ 400 hours/ 12 months

| USE                     | CLIMATE  |
|-------------------------|----------|
| Fuel sulfur level >0,5% | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2  | PRODUCT RECOMMENDATION 3 |
|--------------------------|---------------------------|--------------------------|
| <b>Duranza MSP 0W-30</b> | <b>Presteza MSP 0W-30</b> | <b>Avanza MSP 0W-30</b>  |

Change every 20000 km/ 400 hours/ 12 months

**DIFFERENTIAL REAR (4x2) 450517/2**  
Capacity: 3,1 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1     | PRODUCT RECOMMENDATION 2            |  |
|------------------------------|-------------------------------------|--|
| <b>Gearlube GL-5 85W-140</b> | <b>Unigear LS GL-3/GL-5 85W-140</b> |  |

Change every 80000 km/ 24 months/ 1600 hours

| USE    | CLIMATE |
|--------|---------|
| Normal | Arctic  |

| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2           |  |
|-----------------------------|------------------------------------|--|
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |  |

Change every 80000 km/ 24 months/ 1600 hours

**TRANSMISSION AUTOMATIC ZF 8HP (HI-MATIC) 8/1**  
Capacity: 9,5 liter (Dry fill), Capacity: 3,5-5 liter (Service fill)

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 |  |  |
|--------------------------|--|--|
| <b>SP Matic 2034</b>     |  |  |

Change every 200000 km/ 4000 hours

## IVECO DAILY 72 DAILY 72 C 15 (2014-2016)

**TRANSMISSION MANUAL** FPT 2840.6 OD 6/1

Capacity: 2 liter

| USE                      |                             | CLIMATE  |
|--------------------------|-----------------------------|----------|
| Normal                   |                             | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2    |          |
| <b>SP Gear 5015</b>      | <b>Syngear MT/LD 75W-80</b> |          |

Change every 120000 km/ 2400 hours/ 36 months

**HYDRAULIC BRAKE SYSTEM**

Capacity: 1,11 liter

| USE                              |                           | CLIMATE  |
|----------------------------------|---------------------------|----------|
| Normal                           |                           | Moderate |
| PRODUCT RECOMMENDATION 1         | PRODUCT RECOMMENDATION 2  |          |
| <b>Drauliquid-LV Super DOT 4</b> | <b>Drauliquid-S DOT 4</b> |          |

Check every 40000 km/ 12 months/ 800 hours, change every 24 months

**POWER STEERING**

Capacity: 1,3 liter

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>ATF Dexron II-D</b>   |  |          |

**GREASE POINTS/NIPPLES WHEEL BEARINGS**

| USE                      |                               | CLIMATE  |
|--------------------------|-------------------------------|----------|
| Normal                   |                               | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2      |          |
| <b>Labora Grease</b>     | <b>Multi Purpose Grease 3</b> |          |

**COOLING SYSTEM**

Capacity: 16 liter

| USE                      |                          | CLIMATE                       |
|--------------------------|--------------------------|-------------------------------|
| Normal                   |                          | Moderate                      |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3      |
| <b>Coolant SP 15+</b>    | <b>Coolant SP 12</b>     | <b>Coolant -38 Organic NF</b> |

Check every 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.