

LDV MAXUS MAXUS VAN (70 KW) (<2,8T GVW) (2005-2009)



MOTOR VM R2516L
Kapacitet: 6,5 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Emperol 10W-40

PRODUKTANBEFALING 2

Synfleet SHPD 10W-40

Skift alle 20000 km/ 12 måneder

TRANSAKSEL MANUEL Wia, HTX, PVL 5/1
Kapacitet: 2,35 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

SP Gear 1011

PRODUKTANBEFALING 2

Syngear TDL 75W-90

PRODUKTANBEFALING 3

Syngear 75W-90

Kontroller alle 20000 mil/ 12 måneder

ANVEND
Første skift kun

KLIMA
Moderat

PRODUKTANBEFALING 1

SP Gear 1011

PRODUKTANBEFALING 2

Syngear TDL 75W-90

PRODUKTANBEFALING 3

Syngear 75W-90

Skift alle 20000 km/ 12 måneder

HYDRAULISK BREMSE- & KOBLINGSSYSTEM

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4

Kontroller alle 20000 mil/ 12 måneder, skift alle 24 måneder

SERVOSTYRING

Kapacitet: 0,43 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

ATF Dexron II-D

Kontroller alle 20000 mil/ 12 måneder

LDV MAXUS MAXUS VAN (70 KW) (<2,8T GVW) (2005-2009)



KØLESYSTEM

Kapacitet: 11 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26

Kontroller alle 20000 mil/ 12 måneder, skift alle 100000 mil/ 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.