

LDV PILOTERINGSDIESEL/V200 PILOT 1.9 D VAN 2.6T (2002-2006)



MOTOR DW8

Kapacitet: 4,75 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Asyntho 5W-30

Skift alle 10000 mil/ 12 måneder

DIFFERENTIALE BAG (4x2)

Kapacitet: 1,9 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube LS 80W-90

Kontroller alle 10000 mil/ 12 måneder

GEAR MANUEL R380L 5/1

Kapacitet: 2,4 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 5015

Kontroller alle 10000 mil/ 12 måneder

HYDRAULISK BREMSESYSTEM

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4

Kontroller alle 12 måneder/ 10000 mil, skift alle 24 måneder/ 30000 mil

HYDRAULISK KOBLINGSSYSTEM

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4

LDV PILOTERINGSDIESEL/V200 PILOT 1.9 D VAN 2.6T (2002-2006)



SERVOSTYRING

Kapacitet: 1,1 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

ATF Dexron II-D

Kontroller alle 10000 mil/ 12 måneder

SMØREPUNKTER/NIPLER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

Kontroller alle 10000 mil/ 12 måneder

SVINGTAPHUS

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

Kontroller alle 10000 mil/ 12 måneder

KØLESYSTEM

Kapacitet: 10,6 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26

Kontroller alle 10000 mil/ 12 måneder, skift alle 70000 mil/ 24 måneder

STYRETØJ MANUELT

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Kontroller alle 10000 mil/ 12 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.