

LEYLAND DAF 200 V200 1.9 D (1989-1999)



MOTOR XUD9A
Kapacitet: 5 liter

ANVEND
Normal

KLIMA
Middelhavssagtigt

PRODUKTANBEFALING 1

Bi-Turbo 15W-40

PRODUKTANBEFALING 2

Bi-Turbo 20W-50

PRODUKTANBEFALING 3

Multifleet SHPD 15W-40

Skift alle 10000 km/ 6 måneder

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Asyntho 5W-30

PRODUKTANBEFALING 2

Emperol 10W-40

PRODUKTANBEFALING 3

Synfleet SHPD 10W-40

Skift alle 10000 km/ 6 måneder

ANVEND
Normal

KLIMA
Arktisk

PRODUKTANBEFALING 1

Emperol 5W-40

Skift alle 10000 km/ 6 måneder

DIFFERENTIALE BAG (4x2)

Kapacitet: 1,9 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Kontroller alle 20000 km/ 12 måneder

GEAR MANUEL 5/1

Kapacitet: 2,1 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

ATF-F (Ford)

Kontroller alle 20000 km/ 12 måneder

LEYLAND DAF 200 V200 1.9 D (1989-1999)



HYDRAULISK BREMSESYSTEM

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Skift alle 30000 km/ 18 måneder

HYDRAULISK KOBLINGSSYSTEM

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

SERVOSTYRING

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
ATF Dexron II-D		

Kontroller alle 20000 km/ 12 måneder

SMØREPUNKTER/NIPLER

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Kontroller alle 20000 km/ 12 måneder

SVINGTAPHUS

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Kontroller alle 20000 km/ 12 måneder

LEYLAND DAF 200 V200 1.9 D (1989-1999)



KØLESYSTEM

Kapacitet: 11,3 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26

Skift alle 40000 km/ 48 måneder

STYREHUS

Kapacitet: 0,45 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Kontroller alle 20000 km/ 12 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.