

MERCEDES-BENZ (EU) VIANO 639 VIANO CDI 2.0 DPF (2007-2010)



MOTOR OM646 DE22
Kapacitet: 9 liter

ANVEND

Fleksibel (max)

KLIMA

Moderat

PRODUKTANBEFALING 1

Helar SP LL-03 0W-30

PRODUKTANBEFALING 2

Helar SP LL-03 5W-30

PRODUKTANBEFALING 3

Presteza MSP 5W-30

DIFFERENTIALE BAG
Kapacitet: 1,3 liter

ANVEND

Fleksibel (max)

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 1071

PRODUKTANBEFALING 2

Gearlube LS 80W-90

Skift alle 120 måneder

GEAR AUTOMATISK 722.6xx 5/1
Kapacitet: 7,6 liter (Førstegangsopfyldning)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Matic 4026

Skift alle 120000 km

ANVEND

Første skift kun

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Matic 4026

Skift alle 45000 km/ 24 måneder

GEAR MANUEL 716.652 6/1
Kapacitet: 1,5 liter

ANVEND

Fleksibel (max)

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 5015

Skift alle 120 måneder

MERCEDES-BENZ (EU) VIANO 639 VIANO CDI 2.0 DPF (2007-2010)



HYDRAULISK BREMSE- & KOBLINGSSYSTEM

Kapacitet: 0,8 liter, Kapacitet: 1 liter (Bremsesystem + ESP)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-S DOT 4

Skift alle 24 måneder

SERVOSTYRING

Kapacitet: 0,8-1 liter

ANVEND

Fleksibel (max)

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Matic 4026

PRODUKTANBEFALING 2

SP Matic 2032

KØLESYSTEM

Kapacitet: 8,6 liter, Kapacitet: 10,5 liter (Vito/Viano CDI type 639 + kode H13/HZ7)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 11

PRODUKTANBEFALING 2

Coolant SP 12 EVO

Skift alle 250000 km/ 180 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.