

MITSUBISHI (EU) L300 L300 2.5 D (1987-1992)



MOTOR 4D56

Kapacitet: 4,9 liter, Filterkapacitet: 0,7 liter

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1

Multifleet SCD 30

Skift alle 5000 km/ 6 måneder

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Asyntho 5W-30

PRODUKTANBEFALING 2

Bi-Turbo 15W-40

PRODUKTANBEFALING 3

Synfleet SHPD 10W-40

Skift alle 5000 km/ 6 måneder

DIFFERENTIALE BAG (4x2)

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Kontroller alle 20000 km/ 24 måneder, skift alle 80000 km/ 96 måneder

ANVEND	KLIMA
Normal	Koldt

PRODUKTANBEFALING 1

SP Gear 5015

PRODUKTANBEFALING 2

Gearlube RPC 75W-80

PRODUKTANBEFALING 3

SP Gear 1071

Kontroller alle 20000 km/ 24 måneder, skift alle 80000 km/ 96 måneder

GEAR MANUEL 5/1

Kapacitet: 2 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

SP Gear 1011

PRODUKTANBEFALING 2

SP Gear 5015

PRODUKTANBEFALING 3

Syngear MT/LD 75W-80

Kontroller alle 20000 km/ 24 måneder, skift alle 80000 km/ 96 måneder

MITSUBISHI (EU) L300 L300 2.5 D (1987-1992)



SELVSPÆRRENDE DIFFERENTIALE BAG (4x2)

Kapacitet: 1,8 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Gearlube LS 80W-90		

HYDRAULISK BREMSESYSTEM

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3

Skift alle 40000 km/ 48 måneder

HYDRAULISK KOBLINGSSYSTEM

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3

SERVOSTYRING

Kapacitet: 0,9 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
ATF Dexron II-D		

KØLESYSTEM

Kapacitet: 8,7 liter, Kapacitet: 9,2 liter (+ bageste varmer)

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Coolant -38 Organic NF	Coolant -26	

Skift alle 40000 km/ 48 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.