

# NISSAN (EU) NT400 CABSTAR F23

## CABSTAR 2.0 (F23) (1993-2002)



### MOTOR NA20S

Kapacitet: 3,8 liter, Filterkapacitet: 0,3 liter

| ANVEND | KLIMA            |
|--------|------------------|
| Normal | Middelhavsagtigt |

| PRODUKTANBEFALING 1    | PRODUKTANBEFALING 2          | PRODUKTANBEFALING 3 |
|------------------------|------------------------------|---------------------|
| <b>Bi-Turbo 20W-50</b> | <b>Multifleet SCD 20W-20</b> | <b>HDX 20W-20</b>   |

Skift alle 10000 km/ 6 måneder

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1   | PRODUKTANBEFALING 2    | PRODUKTANBEFALING 3 |
|-----------------------|------------------------|---------------------|
| <b>Emperol 10W-40</b> | <b>Bi-Turbo 15W-40</b> | <b>HDX 20W-50</b>   |

Skift alle 10000 km/ 6 måneder

| ANVEND | KLIMA |
|--------|-------|
| Normal | Koldt |

| PRODUKTANBEFALING 1  |  |  |
|----------------------|--|--|
| <b>Asyntho 5W-30</b> |  |  |

Skift alle 10000 km/ 6 måneder

### DIFFERENTIALE BAG

Kapacitet: 1,3 liter

| ANVEND | KLIMA            |
|--------|------------------|
| Normal | Middelhavsagtigt |

| PRODUKTANBEFALING 1          |  |  |
|------------------------------|--|--|
| <b>Gearlube GL-5 85W-140</b> |  |  |

Kontroller alle 10000 km/ 6 måneder, skift alle 60000 km/ 24 måneder

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1 | PRODUKTANBEFALING 2 | PRODUKTANBEFALING 3        |
|---------------------|---------------------|----------------------------|
| <b>SP Gear 1011</b> | <b>SP Gear 5015</b> | <b>Gearlube RPC 75W-80</b> |

Kontroller alle 10000 km/ 6 måneder, skift alle 60000 km/ 24 måneder

| ANVEND | KLIMA |
|--------|-------|
| Normal | Koldt |

| PRODUKTANBEFALING 1 |  |  |
|---------------------|--|--|
| <b>SP Gear 1081</b> |  |  |

Kontroller alle 10000 km/ 6 måneder, skift alle 60000 km/ 24 måneder

# NISSAN (EU) NT400 CABSTAR F23 CABSTAR 2.0 (F23) (1993-2002)



## GEAR MANUEL 5/1

Kapacitet: 2 liter

| ANVEND                              |  | KLIMA            |
|-------------------------------------|--|------------------|
| Normal                              |  | Middelhavsagtigt |
| PRODUKTANBEFALING 1                 |  |                  |
| <b>Unigear LS GL-3/GL-5 85W-140</b> |  |                  |

Kontroller alle 10000 km/ 6 måneder, skift alle 60000 km/ 24 måneder

| ANVEND              |                     | KLIMA                     |
|---------------------|---------------------|---------------------------|
| Normal              |                     | Moderat                   |
| PRODUKTANBEFALING 1 | PRODUKTANBEFALING 2 | PRODUKTANBEFALING 3       |
| <b>SP Gear 1011</b> | <b>SP Gear 5015</b> | <b>Syngear TDL 75W-90</b> |

Kontroller alle 10000 km/ 6 måneder, skift alle 60000 km/ 24 måneder

| ANVEND              |  | KLIMA |
|---------------------|--|-------|
| Normal              |  | Koldt |
| PRODUKTANBEFALING 1 |  |       |
| <b>SP Gear 1081</b> |  |       |

Kontroller alle 10000 km/ 6 måneder, skift alle 60000 km/ 24 måneder

## HYDRAULISK BREMSE- & KOBLINGSSYSTEM

| ANVEND                           |                           | KLIMA                   |
|----------------------------------|---------------------------|-------------------------|
| Normal                           |                           | Moderat                 |
| PRODUKTANBEFALING 1              | PRODUKTANBEFALING 2       | PRODUKTANBEFALING 3     |
| <b>Drauliquid-LV Super DOT 4</b> | <b>Drauliquid-S DOT 4</b> | <b>Drauliquid DOT 3</b> |

Skift alle 40000 km/ 48 måneder

## SERVOSTYRING

Kapacitet: 0,9 liter

| ANVEND                 |  | KLIMA   |
|------------------------|--|---------|
| Normal                 |  | Moderat |
| PRODUKTANBEFALING 1    |  |         |
| <b>ATF Dexron II-D</b> |  |         |

Kontroller alle 10000 km

## SMØREPUNKTER/NIPLER

| ANVEND               |                                 | KLIMA                        |
|----------------------|---------------------------------|------------------------------|
| Normal               |                                 | Moderat                      |
| PRODUKTANBEFALING 1  | PRODUKTANBEFALING 2             | PRODUKTANBEFALING 3          |
| <b>Labora Grease</b> | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

Kontroller alle 20000 km/ 12 måneder

# NISSAN (EU) NT400 CABSTAR F23

## CABSTAR 2.0 (F23) (1993-2002)



### SMØREPUNKTER/NIPLER HJULLEJER FOR

| ANVEND                                     |  | KLIMA   |
|--------------------------------------------|--|---------|
| Normal                                     |  | Moderat |
| PRODUKTANBEFALING 1                        |  |         |
| <b>Labora Grease</b>                       |  |         |
| <i>Kontroller alle 10000 km/ 6 måneder</i> |  |         |

### KØLESYSTEM

Kapacitet: 8,8 liter, Kapacitet: 9,8 liter (+ varmeapparat)

| ANVEND                                 |                     | KLIMA   |
|----------------------------------------|---------------------|---------|
| Normal                                 |                     | Moderat |
| PRODUKTANBEFALING 1                    | PRODUKTANBEFALING 2 |         |
| <b>Coolant -38 Organic NF</b>          | <b>Coolant -26</b>  |         |
| <i>Skift alle 40000 km/ 48 måneder</i> |                     |         |

### STYREHUS

Kapacitet: 0,7 liter

| ANVEND                                     |  | KLIMA            |
|--------------------------------------------|--|------------------|
| Normal                                     |  | Middelhavsagtigt |
| PRODUKTANBEFALING 1                        |  |                  |
| <b>Unigear LS GL-3/GL-5 85W-140</b>        |  |                  |
| <i>Kontroller alle 10000 km/ 6 måneder</i> |  |                  |

| ANVEND                                     |                     | KLIMA                     |
|--------------------------------------------|---------------------|---------------------------|
| Normal                                     |                     | Moderat                   |
| PRODUKTANBEFALING 1                        | PRODUKTANBEFALING 2 | PRODUKTANBEFALING 3       |
| <b>SP Gear 1011</b>                        | <b>SP Gear 5015</b> | <b>Syngear TDL 75W-90</b> |
| <i>Kontroller alle 10000 km/ 6 måneder</i> |                     |                           |

| ANVEND                                     |  | KLIMA |
|--------------------------------------------|--|-------|
| Normal                                     |  | Koldt |
| PRODUKTANBEFALING 1                        |  |       |
| <b>SP Gear 1081</b>                        |  |       |
| <i>Kontroller alle 10000 km/ 6 måneder</i> |  |       |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.