

NISSAN (EU) NT400 CABSTAR F24 CABSTAR 3.0 DCI DPF EURO 5 (2010-2012)



MOTOR ZD30DDTi

Kapacitet: 11,5 liter, Filterkapacitet: 0,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Armado Synth LSP Ultra 5W-30

Skift alle 30000 km/ 24 måneder

DIFFERENTIALE BAG

Kapacitet: 3-5,1 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

GEAR MANUEL 6/1

Kapacitet: 2,2 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 5015

SELVSPÆRRENDE DIFFERENTIALE BAG

Kapacitet: 3-5,1 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube LS 80W-90

HYDRAULISK BREMSE- & KOBLINGSSYSTEM

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4

NISSAN (EU) NT400 CABSTAR F24 CABSTAR 3.0 DCI DPF EURO 5 (2010-2012)



SERVOSTYRING

Kapacitet: 1 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Matic 2032	ATF Almirol	

SMØREPUNKTER/NIPLER

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

KØLESYSTEM

Kapacitet: 12,5 liter, Kapacitet: 13,2 liter (+ bageste varmer)

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Coolant SP 14+		

Kontroller alle 30000 km/ 24 måneder, skift alle 60000 km/ 48 måneder

ANVEND		KLIMA
Første skift kun		Moderat
PRODUKTANBEFALING 1		
Coolant SP 14+		

Kontroller alle 30000 km/ 24 måneder, skift alle 100000 km/ 60 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.