

# NISSAN (EU) NV200 M20 NV200 1.5 DCI (66 KW) DPF (2009-2013)



## MOTOR K9K

Kapacitet: 4,5-4,8 liter (Servicepåfyldning), Kapacitet: 5,2 liter (Tør efterfyld), Filterkapacitet: 0,1 liter

### ANVEND

Normal

### KLIMA

Moderat

### PRODUKTANBEFALING 1

**Meganza LSP 5W-30**

Skift alle 30000 km/ 12 måneder

### ANVEND

Krævende

### KLIMA

Moderat

### PRODUKTANBEFALING 1

**Meganza LSP 5W-30**

Skift alle 15000 km/ 6 måneder

## TRANSAKSEL MANUEL RS5F92R 5/1

Kapacitet: 2,3 liter

### ANVEND

Normal

### KLIMA

Moderat

### PRODUKTANBEFALING 1

**SP Gear 5015**

Kontroller alle 30000 km/ 12 måneder, skift alle 90000 km/ 36 måneder

## HYDRAULISK BREMSE- & KOBLINGSSYSTEM

### ANVEND

Normal

### KLIMA

Moderat

### PRODUKTANBEFALING 1

**Drauliquid-LV Super DOT 4**

### PRODUKTANBEFALING 2

**Drauliquid-S DOT 4**

Kontroller alle 30000 km/ 12 måneder, skift alle 60000 km/ 24 måneder

### ANVEND

Krævende

### KLIMA

Moderat

### PRODUKTANBEFALING 1

**Drauliquid-LV Super DOT 4**

### PRODUKTANBEFALING 2

**Drauliquid-S DOT 4**

Skift alle 30000 km/ 12 måneder

# NISSAN (EU) NV200 M20 NV200 1.5 DCI (66 KW) DPF (2009-2013)



## KØLESYSTEM

Kapacitet: 6,3-7,1 liter

### ANVEND

Normal

### KLIMA

Moderat

### PRODUKTANBEFALING 1

**Coolant SP 14+**

*Kontroller alle 30000 km/ 12 måneder, skift alle 60000 km/ 48 måneder*

### ANVEND

Første skift kun

### KLIMA

Moderat

### PRODUKTANBEFALING 1

**Coolant SP 14+**

*Kontroller alle 30000 km/ 12 måneder, skift alle 90000 km/ 60 måneder*

## KLIMAANLÆGSSYSTEM

Kapacitet: 450 gram, Kapacitet: 650 gram (med 4-zoners airconditionssystem)

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*