

PEUGEOT J5 J5 1.8 (1000, 1400, 1800) (1987-1990)



MOTOR XM7T/169B

Kapacitet: 4 liter, Filterkapacitet: 0,5 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Specialsynth MSP 5W-40	Emperol 5W-40	Asyntho 5W-30

Skift alle 10000 km/ 12 måneder

TRANSAXSEL MANUEL 4/1

Kapacitet: 1,25 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Gear 5015	Gearlube RPC 75W-80	

Kontroller alle 10000 km, skift alle 40000 km

HYDRAULISK BREMSESYSYSTEM

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Kontroller alle 2500 km, skift alle 40000 km

SERVOSTYRING

Kapacitet: 1,1 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
ATF Dexron II-D		

Kontroller alle 20000 km

KØLESYSTEM

Kapacitet: 9 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Coolant -38 Organic NF	Coolant -26	

Kontroller alle 2500 km, skift alle 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the

PRODUKTANBEFALING

PEUGEOT J5 J5 1.8 (1000, 1400, 1800) (1987-1990)



information contained herein is subject to changes without notification.