

RENAULT (EU) KANGOO II F61 KANGOO II 1.6 8V 90 (2008-2014)



MOTOR K7M
Kapacitet: 3,4 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Duranza LSP 5W-30

PRODUKTANBEFALING 2
Meganza MSP 5W-30

PRODUKTANBEFALING 3
Avanza RPC 5W-30

Skift alle 30000 km/ 12 måneder

ANVEND
Krævende

KLIMA
Moderat

PRODUKTANBEFALING 1
Duranza LSP 5W-30

PRODUKTANBEFALING 2
Meganza MSP 5W-30

PRODUKTANBEFALING 3
Avanza RPC 5W-30

Skift alle 15000 km/ 6 måneder

TRANSAKSEL MANUEL JH3 5/1
Kapacitet: 2,8 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
SP Gear 1081

PRODUKTANBEFALING 2
SP Gear 5015

Kontroller alle 12 måneder/ 30000 km

TRANSAKSEL MANUEL JR5 5/1
Kapacitet: 2,5 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
SP Gear 1081

PRODUKTANBEFALING 2
SP Gear 5015

Kontroller alle 12 måneder/ 30000 km

HYDRAULISK BREMSE- & KOBLINGSSYSTEM
Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2
Drauliquid-S DOT 4

PRODUKTANBEFALING 3
Drauliquid DOT 3

Kontroller alle 30000 km/ 12 måneder, skift alle 24 måneder

RENAULT (EU) KANGOO II F61 KANGOO II 1.6 8V 90 (2008-2014)



SERVOSTYRING

Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

ATF Dexron II-D

Kontroller alle 12 måneder/ 30000 km

KØLESYSTEM

Kapacitet: 5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 16

Kontroller alle 30000 km/ 12 måneder, skift alle 120000 km/ 48 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.