

RENAULT (EU) MASTER II X70 MASTER II 2.5 DCI (88 KW) (2007-2010)

**MOTOR G9U**

Kapacitet: 7,5 liter, Filterkapacitet: 0,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Specialsynth MSP 5W-40

PRODUKTANBEFALING 2

Helar 0W-40

PRODUKTANBEFALING 3

Emperol 5W-40*Skift alle 30000 km/ 12 måneder*

ANVEND

Krævende

KLIMA

Moderat

PRODUKTANBEFALING 1

Specialsynth MSP 5W-40

PRODUKTANBEFALING 2

Helar 0W-40

PRODUKTANBEFALING 3

Emperol 5W-40*Skift alle 15000 km/ 6 måneder***TRANSAKSEL HALVAUTOMATISK PA0 6/1**

Kapacitet: 2,7 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 5015**TRANSAKSEL MANUEL PF6 6/1**

Kapacitet: 2,7 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 5015**HYDRAULISK GEARKASSEBETJENINGSSYSTEM**

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Fluid 3023*Kontroller alle 12 måneder/ 30000 km*

RENAULT (EU) MASTER II X70 MASTER II 2.5 DCI (88 KW) (2007-2010)



HYDRAULISK BREMSE- & KOBLINGSSYSTEM

Kapacitet: 0,7 liter, Kapacitet: 1 liter (ABS)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4

Kontroller alle 30000 km/ 12 måneder, skift alle 120000 km/ 48 måneder

SERVOSTYRING

Kapacitet: 1,1 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Matic 2032

PRODUKTANBEFALING 2

ATF Almirol

Kontroller alle 12 måneder/ 30000 km

KØLESYSTEM

Kapacitet: 10 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 16

Kontroller alle 30000 km/ 12 måneder, skift alle 120000 km/ 48 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.