

RENAULT (EU) MASTER III X62 MASTER III 2.3 DCI 165 FWD DPF X62 (2014-2019)



MOTOR M9T
Kapacitet: 8 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Meganza LSP 5W-30

Skift alle 40000 km/ 24 måneder

ANVEND
Krævende

KLIMA
Moderat

PRODUKTANBEFALING 1
Meganza LSP 5W-30

Skift alle 20000 km/ 12 måneder

TRANSAKSEL HALVAUTOMATISK PA0 6/1
Kapacitet: 2,7 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
SP Gear 5015

TRANSAKSEL MANUEL PF6 6/1
Kapacitet: 2,7 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
SP Gear 1081

PRODUKTANBEFALING 2
SP Gear 5015

HYDRAULISK GEARKASSEBETJENINGSSYSTEM
Kapacitet: 0,5 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
SP Fluid 3023

RENAULT (EU) MASTER III X62 MASTER III 2.3 DCI 165 FWD DPF X62 (2014-2019)



HYDRAULISK BREMSE- & KOBLINGSSYSTEM

Kapacitet: 1 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

Skift alle 120000 km/ 48 måneder

ELEKTRO-HYDRAULISK SERVOSTYRING

Kapacitet: 1,1 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

ATF Dexron II-D

KØLESYSTEM

Kapacitet: 11 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 16

Skift alle 160000 km/ 72 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.