

RENAULT (EU) TRAFIC TRAFIC T 800, T 1000, T 1200 1.6 4X4 (1986-1989)



MOTOR 841/A1M

Kapacitet: 4 liter, Filterkapacitet: 0,25 liter

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Multifleet SHPD 15W-40

PRODUKTANBEFALING 2

Multifleet SHPD 20W-50

Skift alle 7500 km

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Emperol 5W-40

PRODUKTANBEFALING 2

Emperol 10W-40

PRODUKTANBEFALING 3

Bi-Turbo 15W-40

Skift alle 7500 km

ANVEND

Normal

KLIMA

Koldt

PRODUKTANBEFALING 1

Asyntho 5W-30

Skift alle 7500 km

DIFFERENTIALE BAG (4x4)

Kapacitet: 1,3 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 85W-140

PRODUKTANBEFALING 2

Unigear LS GL-3/GL-5 85W-140

Kontroller alle 10000 km, skift alle 50000 km

DIFFERENTIALE FOR (4x2)

Kapacitet: 0,8 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 5015

PRODUKTANBEFALING 2

Gearlube RPC 75W-80

PRODUKTANBEFALING 3

SP Gear 1071

Kontroller alle 10000 km, skift alle 50000 km

ANVEND

Normal

KLIMA

Arktisk

PRODUKTANBEFALING 1

SP Gear 1081

Kontroller alle 10000 km, skift alle 50000 km

RENAULT (EU) TRAFIC TRAFIC T 800, T 1000, T 1200 1.6 4X4 (1986-1989)



GEAR AUTOMATISK

Kapacitet: 2,5 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

ATF Dexron II-D

Skift alle 50000 km

GEAR MANUEL 4/1

Kapacitet: 2,5 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

SP Gear 5015

PRODUKTANBEFALING 2

Gearlube RPC 75W-80

PRODUKTANBEFALING 3

SP Gear 1071

Kontroller alle 10000 km, skift alle 50000 km

ANVEND	KLIMA
Normal	Arktisk

PRODUKTANBEFALING 1

SP Gear 1081

Kontroller alle 10000 km, skift alle 50000 km

HYDRAULISK BREMSESYSYSTEM

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4

PRODUKTANBEFALING 3

Drauliquid DOT 3

Skift alle 50000 km

KØLESYSTEM

Kapacitet: 6 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26

Skift alle 50000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.