

RENAULT (EU) TRAFIC TRAFIC T 900, T 1100 2.0 (1989-1994)



MOTOR J5R.7.16

Kapacitet: 5,5 liter, Filterkapacitet: 0,5 liter

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2
Multifleet SHPD 15W-40	Multifleet SHPD 20W-50

Kontroller alle 3000 km, skift alle 10000 km/ 12 måneder

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Emperol 5W-40	Emperol 10W-40	Bi-Turbo 15W-40

Kontroller alle 3000 km, skift alle 10000 km/ 12 måneder

ANVEND	KLIMA
Normal	Koldt

PRODUKTANBEFALING 1		
Asyntho 5W-30		

Kontroller alle 3000 km, skift alle 10000 km/ 12 måneder

DIFFERENTIALE FOR (4x2)

Kapacitet: 0,8 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Gearlube HS GL-5 80W-140		

Kontroller alle 10000 km/ 12 måneder, skift alle 50000 km/ 36 måneder

GEAR MANUEL 4/1

Kapacitet: 1,7 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
SP Gear 5015		

Kontroller alle 10000 km/ 12 måneder, skift alle 50000 km/ 36 måneder

RENAULT (EU) TRAFIC TRAFIC T 900, T 1100 2.0 (1989-1994)



GEAR MANUEL S5-24 5/1

Kapacitet: 1,8 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 5015

Kontroller alle 10000 km/ 12 måneder, skift alle 50000 km/ 36 måneder

HYDRAULISK BREMSESYSTEM

Kapacitet: 0,7 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4

PRODUKTANBEFALING 3

Drauliquid DOT 3

Skift alle 50000 km/ 36 måneder

KØLESYSTEM

Kapacitet: 7,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26

Skift alle 50000 km/ 36 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.