

SUZUKI SUPER CARRY SUPER CARRY

(1986-1990)



MOTOR F10A

Kapacitet: 3,5 liter, Filterkapacitet: 0,25 liter

ANVEND	KLIMA
Normal	Tropisk

PRODUKTANBEFALING 1

HDX 20W-50

Skift alle 10000 km/ 6 måneder

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Emperol 10W-40

PRODUKTANBEFALING 2

Asyntho 5W-30

Skift alle 10000 km/ 6 måneder

DIFFERENTIALE BAG (4x2)

Kapacitet: 1,3 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Kontroller alle 10000 km/ 6 måneder, skift alle 40000 km/ 24 måneder

ANVEND	KLIMA
Normal	Arktisk

PRODUKTANBEFALING 1

SP Gear 5015

PRODUKTANBEFALING 2

Gearlube RPC 75W-80

PRODUKTANBEFALING 3

SP Gear 1071

Kontroller alle 10000 km/ 6 måneder, skift alle 40000 km/ 24 måneder

GEAR MANUEL 4/1

Kapacitet: 1 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Gearlube GL-4 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

Kontroller alle 10000 km/ 6 måneder, skift alle 40000 km/ 24 måneder

ANVEND	KLIMA
Normal	Arktisk

PRODUKTANBEFALING 1

SP Gear 5015

PRODUKTANBEFALING 2

Syngear MT/LD 75W-80

PRODUKTANBEFALING 3

Syngear 75W-90

Kontroller alle 10000 km/ 6 måneder, skift alle 40000 km/ 24 måneder

SUZUKI SUPER CARRY SUPER CARRY

(1986-1990)

**GEAR MANUEL 5/1**

Kapacitet: 1,3 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-4 80W-90	Unigear HS GL-3/GL-5 80W-90	

Kontroller alle 10000 km/ 6 måneder, skift alle 40000 km/ 24 måneder

ANVEND	KLIMA
Normal	Arktisk

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
SP Gear 5015	Syngear MT/LD 75W-80	Syngear 75W-90

Kontroller alle 10000 km/ 6 måneder, skift alle 40000 km/ 24 måneder

HYDRAULISK BREMSESYSTEM

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Drauliquid DOT 3		

Skift alle 40000 km/ 48 måneder

KØLESYSTEM

Kapacitet: 4 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Coolant -38 Organic NF	Coolant -26	

Skift alle 40000 km/ 48 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.