

# TOYOTA (EU) HI-ACE HI-ACE 2.7I (2007-2012)



## MOTOR 2TR-FE

Kapacitet: 5,5 liter, Filterkapacitet: 0,5 liter

| ANVEND | KLIMA            |
|--------|------------------|
| Normal | Middelhavsagtigt |

| PRODUKTANBEFALING 1    | PRODUKTANBEFALING 2           |
|------------------------|-------------------------------|
| <b>Bi-Turbo 20W-50</b> | <b>Multifleet SHPD 20W-50</b> |

Kontroller alle 3000 km, skift alle 10000 km/ 12 måneder

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1  | PRODUKTANBEFALING 2 |
|----------------------|---------------------|
| <b>Asyntho 5W-30</b> |                     |

Kontroller alle 3000 km, skift alle 10000 km/ 12 måneder

| ANVEND   | KLIMA            |
|----------|------------------|
| Krævende | Middelhavsagtigt |

| PRODUKTANBEFALING 1    | PRODUKTANBEFALING 2           |
|------------------------|-------------------------------|
| <b>Bi-Turbo 20W-50</b> | <b>Multifleet SHPD 20W-50</b> |

Skift alle 5000 km/ 6 måneder

| ANVEND   | KLIMA   |
|----------|---------|
| Krævende | Moderat |

| PRODUKTANBEFALING 1  | PRODUKTANBEFALING 2 |
|----------------------|---------------------|
| <b>Asyntho 5W-30</b> |                     |

Skift alle 5000 km/ 6 måneder

## DIFFERENTIALE BAG

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1         | PRODUKTANBEFALING 2                |
|-----------------------------|------------------------------------|
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |

Skift alle 30000 km/ 48 måneder

# TOYOTA (EU) HI-ACE HI-ACE 2.7I (2007-2012)



## GEAR MANUEL 5/1

Kapacitet: 2,6 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**SP Gear 1011**

PRODUKTANBEFALING 2

**Syngear TDL 75W-90**

PRODUKTANBEFALING 3

**Syngear 75W-90**

*Skift alle 48 måneder*

ANVEND

Krævende

KLIMA

Moderat

PRODUKTANBEFALING 1

**SP Gear 1011**

PRODUKTANBEFALING 2

**Syngear TDL 75W-90**

PRODUKTANBEFALING 3

**Syngear 75W-90**

*Skift alle 60000 km/ 48 måneder*

## TRANSAKSEL AUTOMATISK 5/1

Kapacitet: 8,3 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**SP Matic 2032**

PRODUKTANBEFALING 2

**ATF Almirol**

PRODUKTANBEFALING 3

**ATF Dexron II-D**

*Skift alle 90000 km/ 72 måneder*

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

**SP Matic 2032**

PRODUKTANBEFALING 2

**ATF Almirol**

PRODUKTANBEFALING 3

**ATF Dexron II-D**

*Skift alle 45000 km/ 36 måneder*

## HYDRAULISK BREMSESYSTEM

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Drauliquid DOT 3**

*Skift alle 30000 km/ 24 måneder*

## HYDRAULISK KOBLINGSSYSTEM

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Drauliquid DOT 3**

*Skift alle 24 måneder*

# TOYOTA (EU) HI-ACE HI-ACE 2.7I (2007-2012)



## SERVOSTYRING

Kapacitet: 0,9 liter

### ANVEND

Normal

### KLIMA

Moderat

#### PRODUKTANBEFALING 1

**SP Matic 2032**

#### PRODUKTANBEFALING 2

**ATF Almirol**

#### PRODUKTANBEFALING 3

**ATF Dexron II-D**

*Skift alle 24 måneder*

## KØLESYSTEM

Kapacitet: 15 liter, Kapacitet: 17 liter (med 4-zoners airconditionsystem)

### ANVEND

Normal

### KLIMA

Moderat

#### PRODUKTANBEFALING 1

**Coolant SP 14+**

*Skift alle 90000 km*

### ANVEND

Første skift kun

### KLIMA

Moderat

#### PRODUKTANBEFALING 1

**Coolant SP 14+**

*Skift alle 150000 km*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*