

VOLKSWAGEN (VW) (EU) CADDY 2K/2C CADDY 1.9 TDI (77 KW) 4MOTION (2009-2010)



MOTOR BJB, BLS (PD)
Kapacitet: 4,3 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Presteza MSP 5W-30

PRODUKTANBEFALING 2
Specialsynth MSP 5W-40

Skift alle 15000 km/ 12 måneder

DIFFERENTIALE BAG
Kapacitet: 1,9 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
SP Gear 1011

PRODUKTANBEFALING 2
Syngear TDL 75W-90

TRANSAKSEL HALVAUTOMATISK DSG 02E (DQ250) 6/1
Kapacitet: 7,2 liter (Førstegangsopfyldning), Kapacitet: 5,2 liter (Servicepåfyldning)

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
SP Matic 2072

Skift alle 60000 km/ 48 måneder

TRANSAKSEL MANUEL 02Q 6/1
Kapacitet: 2,3 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
SP Gear 1081

PRODUKTANBEFALING 2
SP Gear 5015

VINKELHJUL/TRANSFERGEARKASSE
Kapacitet: 0,9 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
SP Gear 1011

PRODUKTANBEFALING 2
Syngear TDL 75W-90

Kontroller alle 24 måneder/ 30000 km

VOLKSWAGEN (VW) (EU) CADDY 2K/2C CADDY 1.9 TDI (77 KW) 4MOTION (2009-2010)



HALDEX-KOBLING

Kapacitet: 0,85 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Fluid 6033

Skift alle 36 måneder

HYDRAULISK BREMSESYSYSTEM ABS

Kapacitet: 1,25 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

Skift alle 24 måneder

SERVOSTYRING

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Fluid 3013

KØLESYSTEM

Kapacitet: 8 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 12 EVO

Kontroller alle 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.