

VOLKSWAGEN (VW) (EU) CADDY 2K/2C CADDY 2.0 ECOFUEL (CNG) (2010-2015)



MOTOR BSX
Kapacitet: 4 liter

ANVEND

Forlænget interval (max)

KLIMA

Moderat

PRODUKTANBEFALING 1

Helar SP LL-03 0W-30

PRODUKTANBEFALING 2

Helar SP LL-03 5W-30

Skift alle 30000 km/ 24 måneder

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Helar 0W-40

PRODUKTANBEFALING 2

Emperol 5W-40

PRODUKTANBEFALING 3

Asyntho 5W-30

Skift alle 15000 km/ 12 måneder

TRANSAKSEL MANUEL 0AH (FZT, FZU, GUG, GXZ, JJS, JJT, JJW, KKK, LBP, LBR, LBS, LBT, LBW)
Kapacitet: 2,1 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 1081

PRODUKTANBEFALING 2

SP Gear 5015

Kontroller alle 48 måneder

TRANSAKSEL MANUEL 0AH (KBQ, KHH, KHS, LBU, LBV, MBU) 5/1
Kapacitet: 2,1 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 1081

PRODUKTANBEFALING 2

SP Gear 5015

Kontroller alle 48 måneder

TRANSAKSEL MANUEL FRA OG MED PRODUKTIONSdato 03-1 0AH 5/1
Kapacitet: 2,1 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 1081

PRODUKTANBEFALING 2

SP Gear 5015

Kontroller alle 48 måneder

VOLKSWAGEN (VW) (EU) CADDY 2K/2C CADDY 2.0 ECOFUEL (CNG) (2010-2015)



TRANSAKSEL MANUEL OP TIL PRODUKTIONSDATO 03-12-2 0AH 5/1

Kapacitet: 2,1 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Gear 1081	SP Gear 5015	

Kontroller alle 48 måneder

HYDRAULISK BREMSE- & KOBLINGSSYSTEM

Kapacitet: 1,25 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Drauliquid-LV Super DOT 4		

Skift alle 24 måneder

SERVOSTYRING

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
SP Fluid 3013		

KØLESYSTEM

Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Coolant SP 12 EVO		

Kontroller alle 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.