

VOLKSWAGEN (VW) (EU) LT LT 28(A) 2.8 TDI (1996-1999)



MOTOR AGK

Kapacitet: 7 liter, Filterkapacitet: 1 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Presteza MSP 5W-30

PRODUKTANBEFALING 2

Specialsynth MSP 5W-40

PRODUKTANBEFALING 3

Emperol 5W-50

Skift alle 22500 km/ 12 måneder

ANVEND

Normal

KLIMA

Koldt

PRODUKTANBEFALING 1

Emperol 5W-40

Skift alle 22500 km/ 12 måneder

DIFFERENTIALE BAG (4x2)

Kapacitet: 1,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 1011

PRODUKTANBEFALING 2

Syngear TDL 75W-90

Kontroller alle 45000 km, skift alle 90000 km

GEAR MANUEL 5/1

Kapacitet: 2,2 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 1011

PRODUKTANBEFALING 2

Syngear TDL 75W-90

PRODUKTANBEFALING 3

Syngear 75W-90

Kontroller alle 45000 km, skift alle 90000 km

HYDRAULISK BREMSE- & KOBLINGSSYSTEM

Kapacitet: 2 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4

Skift alle 24 måneder

VOLKSWAGEN (VW) (EU) LT LT 28(A) 2.8 TDI (1996-1999)



SERVOSTYRING

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Matic 4026	SP Matic 2032	

SMØREPUNKTER/NIPLER HJULLEJER FOR

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Skift alle 48 måneder

KØLESYSTEM

Kapacitet: 13 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Coolant -38 Organic NF	Coolant -26	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.