

BAOTIAN BT49QT/50QT BT49QT-10



MOTOR 139QMA
Kapacitet: 0,8 liter

ANVEND	KLIMA
Normal	Middelhavssagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Expulsa RR 15W-50	Expulsa RR 10W-40	Expulsa 10W-40

Skift alle 3000 km/ 3 måneder

ANVEND	KLIMA
Første skift kun	Middelhavssagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Expulsa RR 15W-50	Expulsa RR 10W-40	Expulsa 10W-40

Skift alle 300 km

ANVEND	KLIMA
Andet skift kun	Middelhavssagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Expulsa RR 15W-50	Expulsa RR 10W-40	Expulsa 10W-40

Skift alle 1000 km/ 1 måneder

SLUT-REDUKTION
Kapacitet: 110 cm³

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Gearlube GL-4 80W-90	Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90

Skift alle 5000 km/ 5 måneder

HYDRAULISK BREMSESYSYSTEM
Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Skift alle 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.