

BETA EVO EVO 2T 300 (2014-2014)



MOTOR Beta		
ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Tornado	Scoosynth	Maestrol

GEAR 6 Kapacitet: 0,55 liter		
ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
SP Gear 5015		

Skift alle 1000 km/ 40 timer

ANVEND		KLIMA
Første Service		Moderat
PRODUKTANBEFALING 1		
SP Gear 5015		

Skift alle 5 timer

HYDRAULISK BREMSESYSTEM Kapacitet: 0-0 liter (Imellem min. og max.)		
ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Kontroller alle 1000 km/ 40 timer

HYDRAULISK KOBLINGSSYSTEM Kapacitet: 0-0 liter (Imellem min. og max.)		
ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Kontroller alle 1000 km/ 40 timer

BETA EVO EVO 2T 300 (2014-2014)**SMØREPUNKTER/NIPLER**

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2	

KØLESYSTEM

Kapacitet: 0,42 liter (Servicepåfyldning), Kapacitet: 0,53 liter (Tør efterfyld)

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Coolant SP 11	Coolant SP 12 EVO	

*Kontroller alle 1000 km/ 40 timer, skift alle 2000 km/ 80 timer***FORGAFFEL HØJRE**

Kapacitet: 65 mm (målt komprimeret, uden fjeder)

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Perlus H 32		

Skift alle 2000 km/ 80 timer

ANVEND		KLIMA
Første Service		Moderat
PRODUKTANBEFALING 1		
Perlus H 32		

*Skift alle 1000 km/ 40 timer***FORGAFFEL VENSTRE**

Kapacitet: 125 mm (målt komprimeret, uden fjeder)

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Perlus H 32		

Skift alle 2000 km/ 80 timer

ANVEND		KLIMA
Første Service		Moderat
PRODUKTANBEFALING 1		
Perlus H 32		

Skift alle 1000 km/ 40 timer

BETA EVO EVO 2T 300 (2014-2014)



STØDDÆMPER BAG

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.