

# BETA EVO EVO 2T 80 JUNIOR (2014 OG EFTER)



## MOTOR ZD3 EVO 80

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Tornado**

PRODUKTANBEFALING 2

**Scoosynth**

PRODUKTANBEFALING 3

**Maestrol**

## GEAR 6

Kapacitet: 0,43 liter

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

## HYDRAULISK BREMSESYSTEM

Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Drauliquid-LV Super DOT 4**

PRODUKTANBEFALING 2

**Drauliquid-S DOT 4**

Kontroller alle 1000 km/ 40 timer, skift alle 3000 km/ 120 timer

## HYDRAULISK KOBLINGSSYSTEM

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Drauliquid-LV Super DOT 4**

PRODUKTANBEFALING 2

**Drauliquid-S DOT 4**

Kontroller alle 1000 km/ 40 timer, skift alle 3000 km/ 120 timer

## SMØREPUNKTER/NIPLER

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

## KØLESYSTEM

Kapacitet: 0,6 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Coolant -38 Organic NF**

Kontroller alle 1000 km/ 40 timer, skift alle 2000 km/ 80 timer

# BETA EVO EVO 2T 80 JUNIOR (2014 OG EFTER)



## FORGAFFEL

Kapacitet: 180 cm<sup>3</sup> (hvert ben)

### ANVEND

Normal

### KLIMA

Moderat

### PRODUKTANBEFALING 1

**Perlus H 32**

*Skift alle 2000 km/ 80 timer*

### ANVEND

Første skift kun

### KLIMA

Moderat

### PRODUKTANBEFALING 1

**Perlus H 32**

*Skift alle 1000 km/ 40 timer*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*