

**MOTOR/GEARKASSE**

Kapacitet: 2,3 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Expulsa RR 15W-50*Kontroller alle 3000 km, skift alle 10000 km/ 12 måneder*

ANVEND	KLIMA
Krævende	Moderat

PRODUKTANBEFALING 1

Expulsa RR 15W-50*Skift alle 5000 km/ 3 måneder***HYDRAULISK BREMSESYSTEM**

Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4*Skift alle 12 måneder***SMØREPUNKTER/NIPLER HJULLEJER**

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2*Kontroller alle 10000 km***KØLESYSTEM**

Kapacitet: 1,4 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26*Skift alle 24 måneder*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.