

BMW R SERIER R 1200 R 0A04/0A41 (2015-2018)



MOTOR/GEARKASSE

Kapacitet: 4 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Expulsa RR 5W-40

Kontroller alle 3000 km, skift alle 10000 km/ 12 måneder

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

Expulsa RR 5W-40

Skift alle 500 km

AKSELDREV

Kapacitet: 0,18 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 1011

Skift alle 20000 km/ 24 måneder

HYDRAULISK BREMSESYSTEM

Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4

Skift alle 24 måneder

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4

Skift alle 12 måneder

HYDRAULISK KOBLINGSSYSTEM

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

BMW R SERIER R 1200 R 0A04/0A41 (2015-2018)

**KØLESYSTEM**

Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1**Coolant -38 Organic NF****PRODUKTANBEFALING 2****Coolant -26***Kontroller alle 12 måneder***FORGAFFEL HØJRE**

Kapacitet: 0,59 liter (Førstegangsupfyldning), Kapacitet: 0,68 liter (med elektronisk justeret affjedring)

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

FORGAFFEL VENSTRE

Kapacitet: 0,59 liter (Førstegangsupfyldning), Kapacitet: 0,29 liter (med elektronisk justeret affjedring)

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.