

BOMBARDIER DS DS 250 (2006-2006)



MOTOR

Kapacitet: 1,2 liter, Kapacitet: 1,4 liter (Tør efterfyld)

ANVEND	KLIMA
Normal	Tropisk

PRODUKTANBEFALING 1

Expulsa RR 5W-50

Skift alle 1000 km/ 50 timer

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Expulsa RR 5W-40

Skift alle 1000 km/ 50 timer

ANVEND	KLIMA
Normal	Arktisk

PRODUKTANBEFALING 1

Helar 0W-40

Skift alle 1000 km/ 50 timer

ANVEND	KLIMA
Første Service	Tropisk

PRODUKTANBEFALING 1

Expulsa RR 5W-50

Skift alle 200 km/ 10 timer

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1

Expulsa RR 5W-40

Skift alle 200 km/ 10 timer

ANVEND	KLIMA
Første Service	Arktisk

PRODUKTANBEFALING 1

Helar 0W-40

Skift alle 200 km/ 10 timer

BOMBARDIER DS DS 250 (2006-2006)



SLUTDREV

Kapacitet: 0,18 liter (Servicepåfyldning), Kapacitet: 2 liter (Tør efterfyld)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Gearlube Racing 75W-140		

Skift alle 4000 km/ 24 måneder/ 200 timer

ANVEND	KLIMA
Første Service	Moderat

PRODUKTANBEFALING 1		
Gearlube Racing 75W-140		

Kontroller alle 500 km/ 25 timer

HYDRAULISK BREMSESYSTEM

Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Skift alle 4000 km/ 24 måneder/ 200 timer

KØLESYSTEM

Kapacitet: 0,85 liter (Radiator + motor)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Skift alle 4000 km/ 24 måneder/ 200 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.