

BOMBARDIER OUTLANDER OUTLANDER

330 H.O. 2 X 4 (2004-2005)



MOTOR

Kapacitet: 2,8 liter

ANVEND

Normal

KLIMA

Tropisk

PRODUKTANBEFALING 1

Expulsa RR 5W-50

Skift alle 1500 km/ 50 timer

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Expulsa RR 5W-40

Skift alle 1500 km/ 50 timer

ANVEND

Normal

KLIMA

Arktisk

PRODUKTANBEFALING 1

Helar 0W-40

Skift alle 1500 km/ 50 timer

ANVEND

Første Service

KLIMA

Tropisk

PRODUKTANBEFALING 1

Expulsa RR 5W-50

Skift alle 300 km/ 10 timer

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

Expulsa RR 5W-40

Skift alle 300 km/ 10 timer

ANVEND

Første Service

KLIMA

Arktisk

PRODUKTANBEFALING 1

Helar 0W-40

Skift alle 300 km/ 10 timer

BOMBARDIER OUTLANDER OUTLANDER

330 H.O. 2 X 4 (2004-2005)



DIFFERENTIALE BAG

Kapacitet: 0,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 1011

PRODUKTANBEFALING 2

Syngear 75W-90*Kontroller alle 1500 km/ 50 timer, skift alle 6000 km/ 24 måneder/ 200 timer*

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 1011

PRODUKTANBEFALING 2

Syngear 75W-90*Skift alle 300 km/ 10 timer*

HYDRAULISK BREMSESYSTEM

Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4*Skift alle 6000 km/ 24 måneder/ 200 timer*

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4*Kontroller alle 300 km/ 10 timer*

KØLESYSTEM

Kapacitet: 2,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

PRODUKTANBEFALING 3

Coolant -38 Organic NF*Skift alle 6000 km/ 24 måneder/ 200 timer*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.