

# BUELL M2 CYCLONE M2 CYCLONE (2000-2004)



## ENGINE

Capacity: 2,37 liter, Filter capacity: 0,12 liter

### USE

Normal

### CLIMATE

Mediterranean

### PRODUCT RECOMMENDATION 1

**Bi-Turbo 20W-50***Check every 4000 km, change every 8000 km/ 12 months*

### USE

Acceptable

### CLIMATE

Mediterranean

### PRODUCT RECOMMENDATION 1

**Bi-Turbo 15W-40**

### PRODUCT RECOMMENDATION 2

**Bi-Turbo 20W-50**

### USE

Acceptable

### CLIMATE

Cold

### PRODUCT RECOMMENDATION 1

**Emperol 10W-40**

## TRANSMISSION 5

Capacity: 0,95 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

## HYDRAULIC BRAKE SYSTEM

### USE

Normal

### CLIMATE

Moderate

### PRODUCT RECOMMENDATION 1

**Drauliquid-LV Super DOT 4**

### PRODUCT RECOMMENDATION 2

**Drauliquid-S DOT 4***Check every 8000 km/ 12 months, change every 24 months*

## FRONT FORK

Capacity: 472-473 CM3 (each leg)

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.