

# BUELL XB XB12S LIGHTNING (2004-2008)



## MOTOR

Kapacitet: 2,4 liter

| ANVEND              | KLIMA   |
|---------------------|---------|
| Normal (alternativ) | Moderat |

|                        |  |  |
|------------------------|--|--|
| PRODUKTANBEFALING 1    |  |  |
| <b>Bi-Turbo 20W-50</b> |  |  |

Skift alle 8000 km/ 12 måneder

| ANVEND              | KLIMA            |
|---------------------|------------------|
| Normal (foretrukne) | Middelhavsagtigt |

|                        |  |  |
|------------------------|--|--|
| PRODUKTANBEFALING 1    |  |  |
| <b>Bi-Turbo 20W-50</b> |  |  |

Skift alle 8000 km/ 12 måneder

| ANVEND         | KLIMA            |
|----------------|------------------|
| Første Service | Middelhavsagtigt |

|                        |  |  |
|------------------------|--|--|
| PRODUKTANBEFALING 1    |  |  |
| <b>Bi-Turbo 20W-50</b> |  |  |

Skift alle 1600 km

| ANVEND     | KLIMA            |
|------------|------------------|
| Acceptabel | Middelhavsagtigt |

|                        |                        |  |
|------------------------|------------------------|--|
| PRODUKTANBEFALING 1    | PRODUKTANBEFALING 2    |  |
| <b>Bi-Turbo 15W-40</b> | <b>Bi-Turbo 20W-50</b> |  |

## GEAR 5

Kapacitet: 0,95 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

|                        |  |  |
|------------------------|--|--|
| PRODUKTANBEFALING 1    |  |  |
| <b>Bi-Turbo 20W-50</b> |  |  |

Skift alle 16000 km

| ANVEND         | KLIMA   |
|----------------|---------|
| Første Service | Moderat |

|                        |  |  |
|------------------------|--|--|
| PRODUKTANBEFALING 1    |  |  |
| <b>Bi-Turbo 20W-50</b> |  |  |

Skift alle 1600 km

# BUELL XB XB12S LIGHTNING (2004-2008)



## HYDRAULISK BREMSESYSTEM

Kapacitet: 0,35 liter

| ANVEND                           |                           | KLIMA   |
|----------------------------------|---------------------------|---------|
| Normal                           |                           | Moderat |
| PRODUKTANBEFALING 1              | PRODUKTANBEFALING 2       |         |
| <b>Drauliquid-LV Super DOT 4</b> | <b>Drauliquid-S DOT 4</b> |         |

Kontroller alle 8000 km/ 12 måneder, skift alle 24 måneder

| ANVEND                           |                           | KLIMA   |
|----------------------------------|---------------------------|---------|
| Første Service                   |                           | Moderat |
| PRODUKTANBEFALING 1              | PRODUKTANBEFALING 2       |         |
| <b>Drauliquid-LV Super DOT 4</b> | <b>Drauliquid-S DOT 4</b> |         |

Kontroller alle 1600 km

## FORGAFFEL

Kapacitet: 0,47 liter

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*