

CAGIVA TAMANACO / N90 TAMANACO 125

(1989-1990)



MOTOR + AUTOMATISK SMØRING

Kapacitet: 1,1 liter (Tank)

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Maestrol		

GEAR

Kapacitet: 0,65 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Expulsa RR 15W-50	HDX 15W-40	HDX 20W-50

Kontroller alle 4000 km, skift alle 6000 km

ANVEND		KLIMA
Første skift kun		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Expulsa RR 15W-50	HDX 15W-40	HDX 20W-50

Skift alle 1000 km

HYDRAULISK BREMSESYSTEM

Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Kontroller alle 1000 km

CAGIVA TAMANACO / N90 TAMANACO 125

(1989-1990)



KØLESYSTEM

Kapacitet: 1,2 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26

Kontroller alle 2000 km

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26

Kontroller alle 1500 km

FORGAFFEL

Kapacitet: 80 cm³

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Fork Oil RR 5

Skift alle 10000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.