

DERBI RAMBLA RAMBLA 250I (2010-2014)



MOTOR

Kapacitet: 1,1 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Expulsa RR 10W-40

PRODUKTANBEFALING 2

Expulsa 10W-40

Kontroller alle 5000 km, skift alle 10000 km

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

Expulsa RR 10W-40

PRODUKTANBEFALING 2

Expulsa 10W-40

Skift alle 1000 km

SLUT-REDUKTION

Kapacitet: 0,25 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 1011

PRODUKTANBEFALING 2

Gearlube HS GL-5 75W-90

PRODUKTANBEFALING 3

Syngear 75W-90

Skift alle 10000 km

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 1011

PRODUKTANBEFALING 2

Gearlube HS GL-5 75W-90

PRODUKTANBEFALING 3

Syngear 75W-90

Skift alle 1000 km

HYDRAULISK BREMSESYSTEM

Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

Skift alle 24 måneder

DERBI RAMBLA RAMBLA 250I (2010-2014)



KØLESYSTEM

Kapacitet: 1,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26

Skift alle 24 måneder

FORGAFFEL

Kapacitet: 135 cm3 (hvert ben)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Perlus H 32

Kontroller alle 10000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.