

DINLI DL 702 DL 702 (2008 OG EFTER)



MOTOR

Kapacitet: 3,3 liter (Servicepåfyldning), Kapacitet: 3,5 liter (Tør efterfyld)

ANVEND		KLIMA
Normal		Middelhavsagtigt
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Expulsa RR 5W-50	Expulsa RR 15W-50	Expulsa RR 10W-40

Skift alle 2000 km/ 6 måneder/ 100 timer

ANVEND		KLIMA
Første Service		Middelhavsagtigt
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Expulsa RR 5W-50	Expulsa RR 15W-50	Expulsa RR 10W-40

Skift alle 200 km/ 10 timer

DIFFERENTIALE FOR

Kapacitet: 150 cm³

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Kontroller alle 2000 km/ 6 måneder/ 100 timer, skift alle 24 måneder

SLUTGEAR

Kapacitet: 310 cm³

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Kontroller alle 2000 km/ 6 måneder/ 100 timer, skift alle 12 måneder

HYDRAULISK BREMSESYSTEM

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Kontroller alle 1000 km/ 3 måneder/ 50 timer, skift alle 24 måneder

DINLI DL 702 DL 702 (2008 OG EFTER)



KØLESYSTEM

Kapacitet: 1,6 liter (Motor kun), Kapacitet: 0,35 liter (Tank)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26

Kontroller alle 1000 km/ 3 måneder/ 50 timer, skift alle 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.