

# DUCATI 916 916 BIPOSTO (1994-1998)



## MOTOR/GEARKASSE

Kapacitet: 4 liter, Filterkapacitet: 0,25 liter

| ANVEND                   |                        | KLIMA            |
|--------------------------|------------------------|------------------|
| Normal                   |                        | Middelhavsagtigt |
| PRODUKTANBEFALING 1      | PRODUKTANBEFALING 2    |                  |
| <b>Expulsa RR 15W-50</b> | <b>Bi-Turbo 20W-50</b> |                  |

Kontroller alle 1000 km, skift alle 10000 km

## HYDRAULISK BREMSESYSTEM

| ANVEND                           |                           | KLIMA   |
|----------------------------------|---------------------------|---------|
| Normal                           |                           | Moderat |
| PRODUKTANBEFALING 1              | PRODUKTANBEFALING 2       |         |
| <b>Drauliquid-LV Super DOT 4</b> | <b>Drauliquid-S DOT 4</b> |         |

Kontroller alle 1000 km, skift alle 20000 km

## KØLESYSTEM

Kapacitet: 3,5 liter

| ANVEND                        |                     | KLIMA   |
|-------------------------------|---------------------|---------|
| Normal                        |                     | Moderat |
| PRODUKTANBEFALING 1           | PRODUKTANBEFALING 2 |         |
| <b>Coolant -38 Organic NF</b> | <b>Coolant -26</b>  |         |

Kontroller alle 1000 km, skift alle 20000 km

## FORGAFFEL

Kapacitet: 0,48 liter

| ANVEND                 |                      | KLIMA   |
|------------------------|----------------------|---------|
| Normal                 |                      | Moderat |
| PRODUKTANBEFALING 1    | PRODUKTANBEFALING 2  |         |
| <b>ATF Dexron II-D</b> | <b>Fork Oil RR 5</b> |         |

Skift alle 20000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.