

DUCATI DIAVEL DIAVEL CARBON 1200

(2013-2013)



MOTOR/GEARKASSE

Kapacitet: 4 liter

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Expulsa RR 15W-50

PRODUKTANBEFALING 2

Expulsa RR 10W-40

Skift alle 12000 km/ 12 måneder

ANVEND

Første Service

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Expulsa RR 15W-50

PRODUKTANBEFALING 2

Expulsa RR 10W-40

Skift alle 1000 km

HYDRAULISK BREMSESYSTEM

Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4

HYDRAULISK KOBLINGSSYSTEM

Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4

KØLESYSTEM

Kapacitet: 2,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

Skift alle 24000 km

DUCATI DIAVEL DIAVEL CARBON 1200 (2013-2013)



FORGAFFEL

Kapacitet: 720 cm3 (hver side)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

ATF Dexron II-D

PRODUKTANBEFALING 2

Fork Oil RR 5

Skift alle 24000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.